


Material Safety Data Sheet

RUST OFF

DESCALING

Risk Level

- 4- EXTREME
- 3- SEVERE
- 2- MODERATE
- 1- LIGHT
- 0- NO RISK



I. DEFINITION

NAME OF PRODUCT RUST OFF	CHEMIST Q.B.P. G.Verástegui	DATE OF PREPARATION August 2004
MANUFACTURER Technogreen	ADDRESS 10443 Gulfdale, Suite 102 San Antonio, TX 78216	TELEPHONE Voice: 888-315-0585 Fax: 877-463-5880
DESCRIPTION OF PRODUCT Industrial rust remover		

II. HAZARDOUS INGREDIENTS

CASE No	CHEMICALS	%W	%V	CARCINOGENIC	CASE No	CHEMICALS	%W	%V	CARCINOGENIC
7647-01-0	Hydrochloric Acid	10							
7664-93-9	Sulfuric Acid	10							

III. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR Orange liquid unique strong odor	PH 0.5 +/-1	BOILING POINT (°C) 90 °C
STEAM 68 °C (mm MERCURY) N.A.	VAPOR DENSITY (AIR=1) N.D.	EVAPORATION RATE N.D.
FREEZING POINT (°C) N.D.	SPECIFIC GRAVITY (WATER = 1) 1.110 +/- 0.20 gr/ml	WEIGHT N.A.
		SOLUBILITY Soluble

IV. FIRE AND EXPLOSION

FLAMMABLE (METHOD USED) N.A.	LOWER FLAMMABLE LIMITS N.A.	UPPER FLAMMABLE LIMITS N.A.
MINIMUM EXPLOSION CONCENTRATION N.A.	FLASHPOINT(°C) N.A.	METHOD OF FLASHPOINT N.A.
METHODS OF EXTINCTION X FOAM ALCOHOL FOAM CO ₂ X DRY CHEMICAL POWDER X WATER OTHER		
SPECIAL PROCESS TO FIGHT FIRE PRODUCES DENSE VAPORS		
UNUSUAL RISK OF FIRE AND EXPLOSION N.A.		

V. HEALTH RISKS

TWA HEALTH GUIDE (MAXIMUM EXPOSURE TIME BASED ON AVERAGE WEIGHT IN 8 HOURS OF WORK) N.A.
EFFECTS OF EXPOSURE N.D.
EMERGENCY PROCEDURES INHALATION: Get fresh air and seek medical attention. CONTACT EYES: Flush with plenty of water. See physician if necessary CONTACT WITH SKIN: Wash with plenty of water and apply Vaseline or moisturizing creme INGESTION: Drink milk, take a dose of Activated Charcoal and get immediate medical attention

